



8x 10/100M PoE supported ports

2x Gigabit ports

Main Features

- 8x 10/100M Ethernet ports with PoE support
- 2x 10/100/1000M (Gigabit) Ethernet ports
- IEEE802.3af & IEEE802.3at PoE protocol support
- Maximum 30W power output per interface
- 120W maximum combined power output
- Automatic detection of Powered Devices
- Flow control for Full Duplex operation

Technical Specifications

Network Connections:

Port 1-8:	10/100M with PoE
Port 9-10 (WAN1/2):	10/100/1000M
Transmission distance:	~100m (max.)
Transmission medium:	CAT5/5e/6 standard network cable

Network Switch:

Network Standards:	IEEE802.3/10 BASE-T Ethernet IEEE802.3/100 BASE-TX Ethernet IEEE802.3x Flow Control IEEE802.3az
Maximum Frame Size:	1518 Bytes
MAC address list:	2K
PoE standard:	IEEE802.3af & IEEE802.3at

Power over Ethernet:

PoE Power Supply Type:	End-span (1/2+, 3/6-)
------------------------	-----------------------

Power Supply:

Power Adapter Voltage:	Input: 180-240V AC at 50/60Hz Output: DC 48V
Power Consumption:	125W

Physical Specifications:

Dimensions (WxDxH):	216,8 mm x 159,6 mm x 29,6 mm
Working Temperature:	40°C ~ 55°C (5%-95%)
Storage Temperature:	20°C ~ 70°C
Weight:	1230g